

SDS SAFETY DATA SHEET

SDS Number:
Page 1 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

Section 1 IDENTIFICATION

Product Name: Canvas Epoxy

Manufacturer: Trivantage LLC
1831 North Park Ave
Burlington, NC 27217
800-786-1876
trivantage.com

Trade Name: Canvas Epoxy

Materials Uses: Epoxy RESIN (Part A) used with an Epoxy Hardener (Part B) to Bond Various Substrates.
In Case of Emergency Contact CHEMTREC: (800) 424-9300

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Health Acute Oral Toxicity, Category 4 Skin Corrosion/Irritation, Category 2 Serious eye Damage/Eye Irritation, Category 2A Skin Sensitization, Category 1 STOT SE, Category 3	WARNING WARNING WARNING WARNING WARNING	H302 – Harmful if swallowed H315 – Causes skin irritation H319 – Causes serious eye irritation H317 – May cause an allergic skin reaction H335 – May cause respiratory irritation



GHS Precaution Statements:

Prevention:

- P261 – Avoid breathing dust/fume/mist/vapors/spray.
- P264 – Wash hands (or other affected skin surfaces) thoroughly after handling.
- P270 – Do not eat, drink, or smoke when using this product.
- P273 – Avoid release to the environment
- P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
- P302/P352 – IF ON SKIN: Wash with plenty of soap and water.
- P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:

SDS SAFETY DATA SHEET

SDS Number:
Page 2 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

P403 – Store in a well-ventilated place.
P410 – Protect from sunlight.
P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.

Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.

Ingestion: Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. If vomiting occurs, the head should be kept low so that the stomach vomit doesn't enter the lungs.


Supplemental Information: 90% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture consists of component(s) of unknown acute dermal toxicity. 100% of mixture consists of component(s) of unknown acute inhalation toxicity. 100% of mixture consists of component(s) of unknown acute hazards to the aquatic environment. 15% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Part A RESIN:

HMIS (United States)

Health 2
Flammability 1
Reactivity 0
PPE X

NFPA (United States)



WHMIS (Canada): B2, C, D2B




Part B HARDENER:

HMIS (United States)

Health 2
Flammability 1
Reactivity 0
PPE X

NFPA (United States)



WHMIS (Canada): B2, C, D2B



SDS SAFETY DATA SHEET

SDS Number:
Page 3 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

Part A RESIN:

Name: Mixtures, Adhesives	CAS #	% by Weight
Bisphenol A Epoxy Resin	25068-38-6	80 – 100%
Non-hazardous Ingredients		Not Applicable < 10%

Part B HARDENER:

Name: Mixtures, Adhesives	CAS #	% by Weight
Mercaptan	72244-98-5	84 - 94%
2,4,6-tris-(dimethylaminomethyl)-phenol	90-72-2	6 – 16%

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

Eye: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.

Respiratory: Loosen clothing as necessary and position individual in a comfortable position. Move exposed to fresh air. Give artificial respiration if necessary. If breathing is difficult give oxygen. Immediately get medical assistance.

Ingestion: Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, water spray, fog, dry chemical or CO₂, or alcohol resistant foam.

Specific Hazards Arising from the Chemical: Fire may produce irritating, corrosive and/or toxic gases.

Hazardous Thermal: Decomposition products may include the following materials: Carbon dioxide, carbon monoxide, halogenated compounds.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, and rubber boots. In enclosed spaces, use self-contained breathing apparatus (SCBA) and protective clothing.

Flammability Classification: Combustible, Class IIIB estimated.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Autoignition Temp.: Not Available

LEL: Not Available

UEL: Not Available

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Keep unnecessary personnel away. Avoid contact with skin or inhalation of spillage, dust or vapor. Do not touch damaged containers or

SDS SAFETY DATA SHEET

SDS Number:
Page 4 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Eliminate all sources of ignition. For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid releases to the environment. Retain and dispose of contaminated was water. Keep out of sewers and drains. Contact local authorities if case of spillage to drain/aquatic environment.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well ventilated area.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Part A RESIN:

Material Name:

Bisphenol A Epoxy Resin (CAS: 25068-38-6)

Exposure Limits:

None

Part B HARDENER:

Material Name:

Mercaptan (CAS No: 72244-98-5)

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

Exposure Limits:

None

None

Engineering Controls: Provide adequate ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended.

Respiratory Protection In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

	Part A RESIN	Part B HARDENER
Appearance:	Viscous Liquid	Viscous Liquid
Color:	Clear	Slight Amber
Odor:	Not Available	Mercaptan-like
Odor Threshold:	Not Available	Not Available
pH:	Not Available	Not Available
Melting Point / Freezing Point:	Not Available	Not Available
Initial Boiling Point:	260°C (500°F)	Not Available
Flash Point and Method:	>251°C (>484°F)	>93.3°C (>199.9°F)

SDS SAFETY DATA SHEET

SDS Number:
Page 5 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

	Pensky-Martens Closed Cup: (ASTM D 93)	
Flammability:	Not Available	Combustible, Class IIIB Estimated
Lower Explosion Limit:	Not Available	Not Available
Upper Explosion Limit:	Not Available	Not Available
Vapor Pressure:	.03 mm Hg @ 77°C (171°F)	0.000002hPa Estimated
Vapor Density:	Not Available	Not Available
Relative Density:	1.17 (9.7 lbs./gallon)	1.13 g/cm ³
Solubility in Water:	Negligible	Insoluble
Partition Coefficient (n-Octanol in Water):	Not Available	Not Available
Auto-Ignition Temperature:	Not Available	Not Available
Decomposition Temperature:	Not Available	Not Available
Explosive Properties:	Not Explosive	Not Explosive
Oxidizing Properties:	Not Oxidizing	Not Oxidizing
Viscosity (Dynamic CPS/mPa-s):	8,000 to 10,000 CPS	1,000 – 1,600 mPa-s
Percent Volatile:	Not Available	Not Available
Specific Gravity:	1.17	1.13

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable under normal conditions.

Chemical Stability: The product is stable.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid exposure – obtain special instructions before use. Avoid all possible sources of ignition (spark or flame).

Materials to Avoid (Incompatibility): strong oxidizing materials, strong acids, strong alkalis.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards: Reacts with considerable heat release with some curing agents.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Part A RESIN:

Bisphenol A Epoxy Resin (CAS: 25068-38-6)

LD50 = 11,400 mg/kg (oral, rat)

LD50 = 2,000 mg/kg (dermal, rat)

Conclusion/Summary:

Not Available

Part B HARDENER:

Mercaptan (CAS No: 72244-98-5)

None

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

LD50 = 2,169, oral, rat

Conclusion/Summary:

Not Available

SDS SAFETY DATA SHEET

SDS Number:
Page 6 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information.

Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information.

Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information.

Skin Corrosion/Irritation:

Part A RESIN:

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A Epoxy Resin (CAS: 25068-38-6)	Skin – Erythema/Eschar 404 Acute Dermal Irritation/Corrosion	Rabbit	1.5 – 2		
	Skin – Edema 404 Acute Dermal Irritation/Corrosion	Rabbit	1.0 – 1.5		
	Eyes – 405 Acute Eye Irritation/Corrosion	Rabbit	0		
	Eyes – Redness of the Conjunctivae	Rabbit	0.7		
	Skin – Moderate Irritation	Rabbit		24 hours	
	Skin – Severe Irritant	Rabbit		24 hours	
	Eyes – Mild Irritant	Rabbit			

Part B HARDENER:

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

Causes skin irritation.

Eye Damage / Irritation:

Part A RESIN:

Not Available.

Part B HARDENER:

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

Causes serious eye irritation

Respiratory Sensitization:

Part A RESIN:

Not Available.

Part B HARDENER:

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

Not a respiratory sensitizer.

Skin Sensitization:

Part A RESIN:

Not Available.

Part B HARDENER:

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS No: 90-72-2)

May cause an allergic skin reaction.

Ingestion: Not Available.

Mutagenicity: Not Available.

Carcinogenicity: Not Available.

Reproductive Toxicity: Not Available.

Teratogenic Effects: Not Available.

STOST- Single Exposure:

Part A RESIN:

Product/ingredient name	Category	Route of Exposure	Target Organ
Bisphenol A Epoxy Resin (CAS 26068-38-6)	Category 3		

SDS SAFETY DATA SHEET

SDS Number:
Page 7 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

Part B HARDENER: Not available.

STOST – Repeated Exposure: Not Available.

Aspiration Hazard: Not Available

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be toxic to aquatic organisms and may cause long term adverse effects in an aquatic environment.

Part A RESIN:

Product/ingredient name	Result	Species	Exposure
Bisphenol A Epoxy Resin (CAS 25068-38-6)	Acute LC50 1.3 mg/l - 203 Fish, Acute Toxicity Test	Fish - Fish	96 hour
	Acute EC50 2.1 mg/l - 202 Daphnia sp. Acute Immobilization Test and Reproductive Test	Aquatic invertebrates. Water Flea	48 hour
	Acute No-observable-effect-concentration 0.3 mg/l – 211 Daphnia Magna Reproduction Test	Aquatic invertebrates. Water Flea	21 day
	Acute LC50 > 11 mg/l	Aquatic plants - Algae	72 hour

Part B HARDENER: Not Available.

Persistence and Degradability: Not Available.

Bioaccumulative Potential:

Part A RESIN:

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A Epoxy Resin (CAS 26068-38-6)	2.64 – 3.78	3 – 31 31.00	Low

Part B HARDENER: Not Available.

Mobility in Soil: Not Available.

Other Adverse Effects: No known significant effects or critical hazards.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Part A RESIN/Part B HARDENER: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recycle-able products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14 TRANSPORT INFORMATION

SDS SAFETY DATA SHEET

SDS Number:
Page 8 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

CFR: Not Regulated

TDG: Not Regulated

DOT Classification: Not Regulated

IATA:


IATA:

UN Number: UN3334

UN proper shipping name: Aviation regulated liquid, n.o.s. (Mercaptan-terminated polymer)

Transport hazard class(es):

Class: 9



Subsidiary Risk: -

Packing Group: III

Environmental hazards: No.

ERG Code: 9A

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Other Information:

Passenger and Cargo Aircraft: Allowed with Restrictions.

Cargo aircraft only: Allowed with Restrictions.

IMO:

Marine Pollutant: YES

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification: None required.

United States – TSCA 5(a)2 – Final significant new use rules: Not listed.

United States – TSCA 5(a)2 – Proposed significant new use rules: Not listed.

United States – TSCA 5(e) – Substances consent order: Not listed.

SARA 311/312 Chemical: Yes

Part A RESIN:

Classification Hazard Categories: Immediate (acute) health hazard

Part B HARDENER:

Classification Hazard Categories: Acute Toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization

SDS SAFETY DATA SHEET

SDS Number:
Page 9 of 9

Canvas Epoxy

Revision No.: 1
Revision
Date:06/17/2024

SARA 313 (TRI reporting) Not regulated.
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPS) List: Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.
Safe Drinking Water Act (SDWA): Not regulated.

State Regulations

California Proposition 65: **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Part A RESIN:

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxyethyl)-	Yes	No	5 µg/day	No
Phenol, 4,4'-(1-methylethylidene)bis-	No	Yes	No	No

Part B HARDENER: None Required.

TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

International Regulations:

DSL (Canada Domestic Substance List): All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

EINECS: Not Available.



WHMIS: B2, C, D2B.

Section 16 OTHER INFORMATION

Changes to This Revision: June 17, 2024

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT